



BRAVO 25

BRAVO 25 SPECIFICATIONS (Model 25-210)

ENGINE	Kawasaki FJ180V
TRANSMISSION	Heavy duty 2-speed gear drive transmission
GROUND SPEED	3.0 - 4.2 mph @ 3,500 engine rpm**
WHEEL RATCHET SYSTEM	Integrated within transmission
TRANSMISSION DRIVE	3L Kevlar Belt
CUTTING DECK WIDTH	25"
DECK MATERIAL	14-gauge stamped steel with rolled under lip
BLADE DRIVE SPINDLE	Forged spindle shaft with die cast aluminum housing and permanently lubricated ball bearings
WEAR STRIPS	Replaceable hardened steel strips on both trim sides of mower
CUTTING HEIGHTS	1" - 4.5"
MOWING HEIGHT ADJUSTMENTS	8
WHEELS	Radial shaped 9" semi-pneumatic wheel. Fully interchangeable front and back. Ball bearings in front and fixed to transmission axle in rear.
FRONT AXLE	30 mm steel tube
BAG CAPACITY	2.8 Bushels
MULCH PLUG	Standard
BLADE	Standard
LOWER HANDLE	34 mm aircraft quality aluminum tube with no bolts, brackets or cables on the outside for a snag free smooth exterior
UPPER HANDLE	30 mm aircraft quality aluminum tube shaped to fit operators hands and narrowed to make turning easier
CABLE PROTECTION	Cables are routed within handle tubes for added protection
BLADE CONTROL	BBC
DRY WEIGHT	127 lbs
COMMERCIAL WARRANTY	3 Year Engine / 2 Year Limited Warranty

*Specifications are subject to change without notice. **Ground speeds are approximate measurements.